

Vinyl Duct Tape 3903

Seven for color-coding, holding, and more that remove cleanly





Physical Properties

Adhesion 20 oz./in. width to steel (21 N/100mm) 14 lbs./in. (245 N/100mm) Tensile strenath Up to 250°F (121°C) Use temperature Backing Embossed vinyl Natural rubber Adhesive Tape thickness 6.3mil (0.16mm) Roll length 54.8m (60 yds.) Roll widths/ Green, Black, Gray, Red,

colors White, Yellow, Blue – 48mm (2 in.)

Note: Data should be considered representative or typical only, and should not be used for specification purposes.

These rugged, flexible tapes adhere and conform securely, then remove cleanly from most surfaces for a wide variety of applications.

- 3M rubber adhesive sticks fast and stays fast on many surfaces, even irregular surfaces
- Strong embossed vinyl backing seals out dust, dirt, and moisture, and resists abrasion and many chemicals
- Black tape removes without messy adhesive residue for up to six months; all other colors for up to one month
- Peels off cleanly after one hour on painted steel as hot as 250°F (121°C)
- Easily unwinds from the roll, and if adhesive side should accidentally stick to itself, the fold can be pulled apart to eliminate unusable tangles
- · Tears easily straight across

Application Ideas

- Color-code pipes, conduit, tools, equipment, and more
- Identify tripping hazards
- · General temporary repairs
- · Fine line paint masking
- Protect surfaces from light sand or bead blasting
- · Add decorative trim that also seals

Versatility of 3M[™] Duct Tape 3903

Markets

MRO (Maintenance and Repair)

Construction

Trade Shows and Conventions

General Industrial

Aerospace

Automotive

Specialty and Commercial Vehicles



For temporary labeling and marking 3M[™] Vinyl Duct Tape 3903 removes cleanly without adhesive residue, eliminating mess and cleanup time.


Applications



Bright colors provide good contrast to enhance the visibility of potential tripping hazards. Aggressive adhesive holds tightly even under heavy foot traffic.



For differentiating and identifying tools, select from seven different colors.



WARRANTY AND LIMITED REMEDY: Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

LIMITATION OF LIABILITY: Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Industrial Business Industrial Adhesives and Tapes Division

Building 21-1W-10 900 Bush Avenue St. Paul, MN 55144-1000 1 800 362 3550 www.3M.com/duct